














MIG-F4 series

4K video mosaic box



Magnimage MIG-F4 is a new video box for quad outputs mosaic application. With DP and HDMI inputs, it supports up to 4K*2K@60 Hz 4:4:4 or 8K*1K@60 Hz format source. Its smart control and auto-backup management is a great solution for different big screen project.

Features

-  Quad outputs mosaic
-  Support 4K*2K/60 Hz 4:4:4 input
-  2 DP & 2 HDMI inputs
-  Support 8K x1K@60Hz input
-  EDID management
-  4 DVI or 4 HDMI outputs
-  Customized output resolution
-  Up to 9 million pixel resolution processing capacity
-  Input signal backup
-  Multiple cascade mosaic
-  Save/load preset
-  Image crop, layer zoom
-  Edge blending
-  Controlled by PC software or Android APP
-  Wi-Fi hot spot

Front and rear panel




1 Output status indicators

2 System status indicator

3 Wi-Fi indicator

4 Output synchronization indicator

5 Input status indicators



6 Output 1-4

7 Power switch and port


8 HDMI 1-2 input

9 DP 1-2 input

10 USB port

11 Wi-Fi switch

12 Reset and upgrade



Control mode

PC software: connect MIG-F4 with PC by USB cable. All the settings are done via software.

Android APP: connect MIG-F4 with Android phone by Wi-Fi. All the settings are done via APP.

Operating interface



PC software




Android APP

▣ Main features and applications


▣ Mosaic application 1

Support horizontal pixel to pixel display in 7680 pixel, or upscale horizontal display in 11600 pixel.



▣ Mosaic application 2


Support 4K*2K/60 Hz 4:4:4 input by DP or HDMI for pixel to pixel display.



▮ Main features and applications

🖥️ 8K x 1K / 60Hz input


Support super large resolution 8K×1K/60Hz pixel to pixel input and output display.



▣ Main features and applications


▣ Layer zoom function

Zoom different parts of one 4K*2K input source (with different contents) and display them on different screen.



▣ Same input source to 4 outputs


For 4 screens of different size, you can customize each output's resolution and send the same input source to these screens.



▮ Main features and applications

🖥️ Edge blending mosaic

Single MIG-F4 support up to 4 projectors blending. All the position, size and Gamma of blending area can be adjusted.



Technical parameter

Input parameter		
Port	Quantity	Resolution specifications
DP	2	DP 1.2 support 3840*2160/60Hz and customized resolution
HDMI	2	HDMI 2.0 support 3840*2160/60Hz and customized resolution

Output parameter		
Port	Quantity	Resolution specifications (Single DVI output)
DVI/HDMI	4	Single output port resolution: 1024×768 /60Hz 1366 ×768 /60Hz 1440×900 /60Hz 1280×1024 /60Hz 1680×1050 /60Hz 1600×1200 /60Hz 2560×816 /60Hz 1440 ×1440 /60Hz 1920×1080/60Hz and customized. Widest 2900, highest 2160.



Shenzhen Magnimage Technology Co., Ltd.

Address 8F, Bld. F5, TCL International E City, #1001
Zhongshan Park Road, Nanshan, Shenzhen, China, 518052

Tel 0755- 8664 7651 Fax 0755- 8664 7650

Website: www.magnimage.com